












# CURVED FRAMING SPECIFICATIONS

<b>GAUGES:</b>	20, 18, 16, & 14	<b>TOLERANCES:</b>	1/8" per 10'-0"
<b>WEB WIDTHS:</b>	Up to 12"	<b>MINIMUM RADIUS:</b>	12" Custom Approx. 24" Standard
<b>FLANGES:</b>	Up to 3"	<b>COATINGS:</b>	G60 & G90
<b>MATERIAL TYPES:</b>	Track, Slotted Track, Stud, Angle, Hat Channel, Z-Furring, & CRC	<b>KSI:</b>	33 & 50
<b>LENGTHS:</b>	Up to 35'-0"	<b>OTHER MATERIALS:</b>	Stainless, Steel, Aluminum

<b>BENDING TYPES:</b>	Curved Part Identification		Radius Measurement location 		For the fastest lead time, select 10' part lengths For the cheapest shipping, select part lengths 16' or less	
	 Track Bend	 Slotted Track Bend	 Track Crimp	 Track 18 ga min   Roll	 Z Purlin 18 ga min   Roll	
	 Stud Bend	 Angle Crimp	 Angle 18 ga min   Roll	 Hat Channel Crimp	 Hat Channel Roll	

Not all listed gauges, web widths, flanges sizes, and material lengths are available in or with all material types or curved types. Listed minimum radii do not apply to all material types, sizes, gauges, and curve types.

Please call Radius Track Corporation for specification details for your specific applications:  
+1 (763) 759-8885 or Toll-Free: +1.888.872.3487